



Physical Specification

Model	Active Size (HxW mm)	External Size (HxWxD mm)	Packing Size (HxWxD cm)	Aspect Ratio	NW. (Kgs)	GW. (Kgs)	Hotkeys
ST-9400U-83	1692 x 1194(81.5")	1723.4 x 1225.4 x 22 (83.3")	182 x 129 x 7.5	4:3	13.0	16.6	Left & Right
ST-9400U-88	1937 x 1040(86.6 ")	1968.4 x 1071.4 x 22 (88.2")	207 x 113 x 7.5	16:9	13.2	17.0	Left & Right
ST-9400U-96	2100 x 1125(93.8")	2131.4 x 1156.4 x 22 (95.5")	223 x 122 x 7.5	16:9	15.1	20.7	Left & Right
ST-9400U-101	2222 x 1194(99.3")	2253.4 x 1225.4 x 22 (101.0")	235 x 129 x 7.5	16:9	16.7	23.3	Left & Right



Technical Specification

Touch Spec	
Touch Technology	Infrared
Touch Points	10 Touches
Touch Resolution	32767 x 32767
Coordinate Accuracy	≥1mm
Tracking Speed	8m/s
Transmitting Speed	12M/s
Cursor Speed	180pps
Response Time	≤7ms
Input Method	Finger, Stylus
Interface	USB 2.0/3.0
Support OS.	Windows XP/VISTA/7/8/10, MAC, LINUX, Android
Mechanical	
Middle Board Material	Nanometer High Polymer Surface +Aluminum Honeycomb Enamel Porcelain +Aluminum Honeycomb (Optional)
Projection Effect	Excellent With Low Glare
Viewable Angle	Left & Right: 170° / On & Under: 160°
Environmental	
Working Temperature	-15°C~+55°C
Working Humidity	20-90%
Storage Temperature	-40°C~+70°C
Storage Humidity	10-90%
Electrical	
Power Supply	DC 5V via PC USB Port
Input Voltage	DC 4.6V ~ DC 5V
Working Current	≤110mA
Power Consuming	≤2W
Accessories	
Stylus Markers	Black/Green/Red
Wall Mount Brackets	1 set (Including Screws)
Software CD	1 pcs
USB Cable	5m
Mobile Floor Stand	Optional
Certificate	CE, FCC, ROHS
Warranty	3 Year Limited